

Data Sheet

0370 Fine Ribbed/Fluted Rubber (SBR) Matting

Data Sheet Type	Final
Material Reference	0370
Polymer	SBR
Date Issued	21/05/24



Description

A General Purpose Matting with a Fine Ribbed Surface, suitable as a floor covering for temporary or semi-permanent use in industrial & commercial areas. Can also be converted for Shelf or Drawer Liners in Industrial/Workshop environments.

Specifications	Values	Test Methods
Compression Set(22 Hours @ 70°C)	30 % Maximum	ASTM D395 Method B
Elongation at Break	250 % Minimum	ASTM D412
Highest Recommended Working Temperature	70 °C Maximum	None
Intermittent Working Temperature	90 °C Short Bursts Only	None
Lowest Recommended Working Temperature	-20 °C Minimum	None
Specific Gravity	1.5 g/cm 3 +/-0.05	ASTM D2240
Tensile Strength	2.8 MPA Minimum	ASTM D412

Important Notes about this Material Data Sheet

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information, figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice . All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.