

A reusable and highly effective mat for preventing spilt oils and chemicals entering the drainage system. The durable polyethylene top is flexible and resistant to abrasions. The underside is sticky to tightly seal the drain. The cover is manufactured using a bonded nylon, providing extra strength with carry handles for ease of handling and deployment. Can be reused by cleaning with soap and water before storing.

## Data Sheet Data Sheet Type Final Material Reference Polymer Date Issued 4610-120L-Mat Flexible Drain Mat with Carry Handles 4610-120L-Mat Flexible Drain Mat with Carry Handles

| Specifications                | Values           | Test Methods |
|-------------------------------|------------------|--------------|
| Anti Static                   | No               | None         |
| Colour                        | Yellow           | None         |
| For Use With                  | Oils & Chemicals | None         |
| Size                          | 120cm x 120cm    | None         |
| Thickness                     | 8 mm             | ASTM D792    |
| Water Repellant (Hydrophobic) | Yes              | None         |
| Weight                        | 12.8 KG          | None         |

## Purposes







Chemical Resistant

Oil Resistance

Petrol Resistance

## Important Notes about this Material Data Sheet

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information, figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice. All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.