

## Data Sheet

## C047 Neoprene with Anti-Wicking Nylon Insertion

Data Sheet Type	Final
Material Reference	C047
Polymer	CR
Date Issued	29/09/20



## Description

A Neoprene Coated Nylon Cloth with Anti Wicking.

Specifications	Values	Test Methods
Coat Material	Neoprene	None
Coat Weight Per Side	0.750 g/cm <sup>2</sup>	None
Coated Fabric Weight	0.1925 g/cm <sup>2</sup>	None
Colour	Black	None
Fabric Weave Pattern	Plain	None
Fabric Weight	425 g/cm <sup>2</sup>	None
Highest Recommended Working Temperature	120 °C	None
Standard Roll/Sheet Size	1500mm Wide Usable Range	None
Thickness	1.5 mm	ASTM D792
Warp	5200N/50mm	None
Weft	4500N/50mm	None

**Important Notes about this Material Data Sheet**

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information, figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice. All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.