

## Data Sheet

## Diamond Plate Anti-Fatigue Rubber mats

Data Sheet Type	Final
Material Reference	Diamond
Polymer	PVC
Date Issued	27/07/24

## Description

Our Diamond Plate PVC Antifatigue Runners are available with 3 options of Underlay.

- \* Urethane for Recycled and Economy
- \* Closed Cell PVC for Anti-fatigue
- \* Nitricell ® fro Resilience and Oil Resistance

These runners are suitable for Short or Long Runs in Warehouses, Factories etc.

Specifications	Values	Test Methods
Flame Resistance	A Rated Underlay EN13501-CS1	FMVSS302
Slip Resistance	Dry 0.68	ASTM D575-01

## Purposes



Abrasive Resistance



Flame Retardent



Self Extinguishing

**Important Notes about this Material Data Sheet**

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information,

---

figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice . All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.