

Data Sheet

PDA17MB200BG

Data Sheet Type	Final
Material Reference	PDA17MB200B G
Polymer	
Date Issued	16/07/24



Description

Anti Static Oil absorbent pads offering maximum absorbent capacity and retention. These pads offer rapid capillary action and are used where flammable vapours are present and static electricity needs to be safely dissipated. Pack Quantity 200

Specifications	Values	Test Methods
Anti Static	Yes	None
Colour	White	None
For Use With	Oil	None
Maximum Absorbency	185 L	None
Size	40 x 50cm	None
Water Repellant (Hydrophobic)	Yes	None
Weight	7.2 KG	None

Important Notes about this Material Data Sheet

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information, figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice. All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.