

Data Sheet		Solid Vinyl Modular Tile	
Data Sheet Type	Final		
Material Reference	Solid Tile	OE IN THE	741 - 20m
Polymer			REACH
Date Issued	16/07/24	W D	

## Description

A Solid Vinyl Modular Floor Tile for heavier duty applications where fork trucks, pallet trucks are operating, and stillages and heavy loads located.

Manufactured 500mm x 500mm x 7mm thick with interlocking dovetails the tile is perfect for protecting floors in warehouses, factories garages, exhibition halls and sport & leisure facilities. The mat is easy to lay and will go over most surfaces to give the ground a smooth and level finish.

These Solid Vinyl tiles are high quality, durable and fire retardant, and 100% recyclable.

Specifications	Values	Test Methods
Flame Resistance	Bfl-S1	None
Flexibility	No Cracking °C	None
Highest Recommended Working Temperature	50 °C	None
Load Weight	3350 Maintained for 2 Hours on a solid base KG	None
Lowest Recommended Working Temperature	-20 °C	None
Slip Resistance	DS R10	None
Total Weight	2.4 KG	None

## Purposes







Flame Retardent

Water Resistant

Weather Resistance

## **Important Notes about this Material Data Sheet**

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information,



figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice. All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.