

Data Sheet

Viton Caulk

Data Sheet Type	Final
Material Reference	TBA0000999
Polymer	FKM(<66% Flourine)
Date Issued	16/05/24



Description

Viton™ Fluorodyn™ Caulk Sealant

This revolutionary caulk based on Viton™ fluoroelastomer produced in conjunction with The Chemours Company provides excellent sealing for flanges lining for pipes and thermal power station flues.

Fluorodyn® Caulk made with Viton™ is compounded with 75% Solids making it an easy to apply single component Caulk.

It is resistant even in its uncured state to virtually all Chemicals including Nitric, Sulphuric and Hydrochloric Acids.

Supplied in 71ml, 320ml and 850ml caulking tubes for use with a Caulking/Sealant Gun.

- Chemical & Corrosion Resistance
- Aliphatic, aromatic and halogenated hydrocarbon resistance
- Expansion Joint Repair
- Repair of Vion™ parts
- UV Ray & Ozone Resistance
- Environment Protection
- Adhers to all metals, concrete, glass and ceramics
- High Temperature
- Sealing Flanges and Expansion Joints
- Bolt Sealant

Purposes



Acid Resistance


Bio-Fuel
Resistance

Chemical
Resistant

High Working
Temperature


Oil Resistance



Ozone Resitance



Steam Resistant	Weather
	Resistance

Important Notes about this Material Data Sheet

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information, figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice. All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.