

Data Sheet

4000/X Disposable Drain Cover Mat

Data Sheet Type	Final
Material Reference	4000/X-Mat
Polymer	
Date Issued	26/12/24



Description

A reinforced clay mat designed to effectively prevent spilt oils and chemicals flowing through storm drains into controlled waters. Provides up to 24 hours resistance to most oils and chemicals enabling a planned clean up of spills. Flexible down to temperatures of -20c and suitable for use on damaged drains and rough surfaces, impregnated with a anti-freeze and anti-mould additive. Can be overlapped to seal off larger areas. Pack of 2 Mats

Specifications	Values	Test Methods
Colour	Grey	None
For Use With	Oils & Chemicals	None
Size	65cm x 45cm	None
Water Repellant (Hydrophobic)	Yes	None
Weight	12.9 KG	None

Purposes



Chemical Resistant



Oil Resistance



Petrol Resistance

Important Notes about this Material Data Sheet

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information, figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice. All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.