

Data Sheet

Elevate AFR FoodSafe Matting

Data Sheet Type	Final
Material Reference	Elevate AFR
Polymer	PVC
Date Issued	30/10/24



Description

Elevate AFR is a high visibility matting designed specifically to perform in the highly regulated food processing and preparation industries.

Supplied in rolls 10mtr long x 91cm wide with easy snap connectors to allow multiple rolls to be linked together to cover longer or wider areas.

Manufactured from a flexible animal fat resistant PVC infused w/anti-microbial and anti-fungal additive so it is resistant to animal fats and oils. Designed with a 2.9cm x 1.9cm widely spaced grid which enables fluids and by-products to fall through while elevating employees above it. Elevate AFR is up to 65% lighter than conventional rubber drainage mats so it is easy to install, clean, roll up and move.

Specifications	Values	Test Methods
Coefficient of Sliding Friction	0.82 / 0.67 Dry / Wet	None
Highest Recommended Working Temperature	60 °C	None
Lowest Recommended Working Temperature	-22 °C	None
Thickness	16mm	None

Purposes



Food Contact Suitability



Water Resistant



Wear Resistant

**Important Notes about this Material Data Sheet**

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information, figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice. All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.