

Data Sheet **Ergodeck ® Modular PVC Durable Flooring Tile System**

| | |
|--------------------|----------|
| Data Sheet Type | Final |
| Material Reference | TOUGH |
| Polymer | PVC |
| Date Issued | 23/11/24 |

Description

The Ultimate Modular Flooring Tile System for both general purpose and Anti-Fatigue use.

Available in different polymers designed for comfort or durability, in an open and closed design, this tiling system is the choice for many environments.

Use in Warehouses, Factories, Assembly Lines and in any area that requires a professional finish with a product that will last.

This product is Silicone Free so is suitable for Paint Shops.

Tile size = 457mm x 457mm x 22mm - Ramped Edges and Corners Available.

| Specifications | Values | Test Methods |
|------------------|-------------------|--------------|
| Flame Resistance | A Rated | FMVSS302 |
| Slip Resistance | Dry 0.65 Wet 0.42 | ASTM D575-01 |
| Total Weight | 2.5 KG | None |

Purposes



Abrasive Resistance



Chemical Resistant



Flame Retardant



Oil Resistance



Ozone Resistance



Self Extinguishing



Water Resistant



Wear Resistant



Weather Resistance

Important Notes about this Material Data Sheet

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information, figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice. All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.