

| Data Sheet | | MacMat-SD | |
|--------------------|-----------|-----------|--------------|
| Data Sheet Type | Final | | |
| Material Reference | MacMat-SD | | AND DO DO DO |
| Polymer | PVC | | REACH |
| Date Issued | 17/09/25 | | |

Description

MacMat-SD is a high grade PVC matting, weather resistant and Fire Rated to UL94 V0. Manufactured with High Visibility Yellow and Green Bars to assist with Social Distancing Queuing at 1mtr and 2mtr intervals or with High Visibility Blue Bars for Social Distancing between Work Stations.

The printed text can be bespoke to your requirements subject to minimum production batches and lead times.

Offered in standard rolls of 10mtr x 1.2mtr wide and either 3.5mm or 6mm thickness dependent upon your environment and level of footfall.

| Specifications | Values | Test Methods |
|---|------------|--------------|
| Elongation at Break | 300 % | None |
| Flame Resistance | V0 | UL94 |
| Highest Recommended Working Temperature | 60 °C | None |
| Lowest Recommended Working Temperature | -30 °C | None |
| Specific Gravity | 1.2 g/cm 3 | None |
| Tensile Strength | 5 MPA | None |

Purposes



Flame Retardent



Wear Resistant



Important Notes about this Material Data Sheet

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information, figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice. All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.