

Data Sheet P035 Graphite/PTFE Braided Packing for High Speed Pumps

|                    |                     |
|--------------------|---------------------|
| Data Sheet Type    | Final               |
| Material Reference | P035                |
| Polymer            | Graphite/PTFE Blend |
| Date Issued        | 03/06/26            |



Description


A high performance multi-filament Graphited PTFE Packing impregnated with High Temperature Lubricant. Recommended for its excellent performance at high pressure and its anti-extrusion properties.

| Specifications                          | Values        | Test Methods |
|---|---------------|--------------|
| Highest Recommended Working Temperature | 280 °C        | None         |
| Lowest Recommended Working Temperature  | -100 °C       | None         |
| Maximum Linear Speed                    | 1 m/s         | None         |
| Maximum Rotary Pressure                 | 20 bar        | None         |
| Maximum Rotary Speed                    | 20 m/s        | None         |
| Maximum Valve Pressure                  | 200 bar       | None         |
| PH Range                                | 1-14 PH Range | None         |

Purposes



Chemical Resistant



High Working Temperature



Low Working Temperature



Oil Resistance



Petrol Resistance

**Important Notes about this Material Data Sheet**

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information, figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice. All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.