

Data Sheet		SPIL-MRA24MD001BG	
Data Sheet Type	Final		
Material Reference	MRA24MD001BG	DE IN THE	REACH
Polymer			
Date Issued	19/11/25	V. N	

Description

Anti Static Oil absorbent Roll offering maximum strength, absorbent capacity and retention. These Rolls are manufactured from melt blown fibres and ultrasonically bonded creating a dimpled surface and are used where flammable vapours are present and static electricity needs to be safely dissipated. Pack Quantity 1

Specifications	Values	Test Methods
Anti Static	Yes	None
Colour	White	None
For Use With	Oil	None
Maximum Absorbency	124 L	None
Size	50cm x 45m	None
Water Repellant (Hydrophobic)	Yes	None
Weight	5.4 KG	None

Important Notes about this Material Data Sheet

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information, figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice. All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.