

Data Sheet		SPIL-PDW24SL100BG Oil Absorbent Pad	
Data Sheet Type	Final		
Material Reference	PDW24SL100BG	OE IN THE	MINI COMO
Polymer		N A	REACH
Date Issued	02/09/25	M N	

Description

Oil Absorbent Pads manufactured from melt blown polypropylene fibres, ultrasonically bonded and laminated with a spunbond layer on one side to improve tear resistance. Delivering excellent absorbency and fluid retention. Absorbency Tested to BS7959-1:2004 This product can be incinerated, allowing you to reduce disposal costs. Pack Quantity 100

Specifications	Values	Test Methods
Anti Static	No	None
Colour	White	None
For Use With	Oil	None
Maximum Absorbency	117 L	None
Size	40 x 50cm	None
Water Repellant (Hydrophobic)	Yes	None
Weight	5 KG	None

Purposes



Oil Resistance

Important Notes about this Material Data Sheet

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information, figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice. All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.